Fractal approaches to combat modelling

Dr Michael Lauren

maintaining the data needed, and of including suggestions for reducing	llection of information is estimated to completing and reviewing the collect this burden, to Washington Headquuld be aware that notwithstanding an OMB control number.	ion of information. Send comments arters Services, Directorate for Info	regarding this burden estimate ormation Operations and Reports	or any other aspect of to the state of the s	his collection of information, Highway, Suite 1204, Arlington		
1. REPORT DATE 2. REPORT TYPE 01 OCT 2003 N/A				3. DATES COVERED -			
4. TITLE AND SUBTITLE			5a. CONTRACT NUMBER				
Fractal approaches	s to combat modelli	5b. GRANT NUMBER					
		5c. PROGRAM ELEMENT NUMBER					
6. AUTHOR(S)		5d. PROJECT NUMBER					
					5e. TASK NUMBER		
					5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Defence Technology Agency					8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)					10. SPONSOR/MONITOR'S ACRONYM(S)		
		11. SPONSOR/MONITOR'S REPORT NUMBER(S)					
12. DISTRIBUTION/AVAIL Approved for publ	LABILITY STATEMENT lic release, distributi	on unlimited					
13. SUPPLEMENTARY NO See also ADM0019 contains color image	29. Proceedings, He	ld in Sydney, Austr	alia on July 8-10,	2003., The o	riginal document		
14. ABSTRACT							
15. SUBJECT TERMS							
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON		
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified	UU	18	RESPUNSIBLE PERSUN		

Report Documentation Page

Form Approved OMB No. 0704-0188

Drivers

- Lack of models available. Simple "Lanchester" approaches the principal option
- Had a broad range of problems, including issues such as Recce and C2
- Agent-based models seemed like a good approach but not "Physics based"

Origins of our approach

- The physics of weather: more detail does not give better answers
- Simple fractal models seem to better reproduce statistics of weather than supercomputers
- Differential equations do not seem to be able to describe complex systems
- Self-organisation important

Hypothesis

- Assume combat is a selforganising system
- Further assume combat data can be characterised in terms of fractal dimensions
- Then, fractal dimension of combat data can be related to the attrition function

Blue attrition

Function of:

- Number of Red
- Time
- Kill probabilities
- Fractal dimension of distribution


$$\frac{\Delta B}{\Delta t} = f(R, t, k_r, D)$$

A convenient form is:

$$\left\langle \frac{\Delta B}{\Delta t} \right\rangle \propto R k_r^{E(D)} \Delta t^{-F(D)}, \quad E+F=1$$


- Two parts: k and t
- Ensemble of runs with similar distribution of Red.
- Can choose by requiring a minimum casualty level.
- Reduces to the Lanchester equation.

Fractal pattern (MOUT)




The k part:

Different patterns for different behaviours, implies differing attrition rates.




The t part:

- Implies that the attrition function itself should have a specific temporal structure.
- Should be intermittent and clustered i.e. when it rains it pours.




Historical data confirms our hypothesis!



Applications

Has implications for C2 and logistic loads etc.

$$c = \left(\frac{P}{1.68}\right)^{-0.4}$$



Casualty estimation

Percentile	Normalized estimate	Actual 1st Inf Div estimate (actual)	Actual 2 nd Inf Div estimate (actual)	Actual 4th Inf Div estimate (actual)	Actual 2 nd Arm Div estimate (actual)
90%	3.1	98 (92)	110 (88)	206 (186)	61 (64)
95%	4.1	130 (100)	145 (130)	271 (253)	81 (95)
99%	7.8	248 (159)	278 (319)	517 (470)	154 (160)
Mean	1.0	31.8	35.6	66.4	19.8

Understanding historical results

 $C = (Number of attackers/Number of defenders)^{0.685}$


- Thornton (UK)
- Osipov (Russia)
- Helmbold (US)

Inconsistent with Lanchester!


Fractal idea

- Check with agent-based models
- Behaviour (tactics) causes battles to evolve in similar (but not exactly the same) ways
- Could there be a fractal attractor at work?

Battles evolve into an attractor with the same fractal dimension for the same types of battles (related to ideas proposed by Jim Moffat)



Find values for *D*:



What this gives us

- Fractal nature of combat data tells us our models need to produce output consistent with fractals
- Thus, fractals provide a method by which we can judge if the complexity is being characterised properly by our models
- Can characterise sophisticated differences in forces by a single parameter!

29/08/2007